



# STAS j-rail

## professional versatility

The design of STAS j-rail was based on the shape of the letter J. This shape allows the rail to be combined in all kinds of different ways using hooks, cords and even rods.

For example, by using a rod instead of a cord or steel cable, moving or alternating works of art on high ceilings becomes a piece of cake. You won't need a ladder, because the rod can be lifted out of the rail from below.

STAS j-rail has a somewhat industrial look and is applied regularly in art galleries and in business premises.

- dimensions 7 x 20 mm
- length 150, 200 or 300 cm
- aluminium
- white or alu
- wall mountable, not adjoining to ceiling
- weight capacity 25 kg/m
- 5 years warranty



### Parts

#### STAS j-rail

RJ10115 150 cm white  
RJ10120 200 cm white  
RJ10130 300 cm white

RJ30115 150 cm alu  
RJ30120 200 cm alu  
RJ30130 300 cm alu

(4 holes per m<sup>2</sup>)



**STAS j-rail  
screw flush head**  
SJ10100 white  
SJ30100 alu

**STAS plug**  
SR50700



# STAS j-rail

## hooks, cords and rods

STAS j-rail has its own set of hooks, cords and rods with which to complete the system.

### Cords, rods and rail hooks



**STAS cylinder hook**  
HR10600 white  
HR30600 alu



**STAS steel cable with glider**  
SH10110 100 cm  
SH10115 150 cm  
SH10120 200 cm  
SH10125 250 cm  
SH10130 300 cm  
SH10145 450 cm



**STAS j-rail rod 3 mm**  
SO10110 100 cm white  
SO10115 150 cm white  
SO10120 200 cm white  
SO10130 300 cm white  
  
S030110 100 cm alu  
S030115 150 cm alu  
S030120 200 cm alu  
S030130 300 cm alu



**STAS perlon cord with loop**  
PL10110 100 cm  
PL10115 150 cm  
PL10120 200 cm  
PL10125 250 cm  
PL10130 300 cm



**STAS j-rail s-hook**  
HR10400 white  
HR30400 chromo

#### STAS perlon cord with glider

PH10110 100 cm  
PH10115 150 cm  
PH10120 200 cm  
PH10125 250 cm  
PH10130 300 cm  
PH10145 450 cm

#### STAS steel cable with loop

SL10110 100 cm  
SL10115 150 cm  
SL10120 200 cm  
SL10125 250 cm  
SL10130 300 cm



### Hooks



**STAS smartspring**  
HA30900



**STAS zipper**  
HA30501



**STAS zipper pro**  
HA30530



**STAS j-rail spring hook**  
HA30700



### Possible combinations



max.  
4 kg

**j-rail s-hook + perlon cord with loop + smartspring, zipper or zipper pro**



max.  
15 kg

**j-rail s-hook + steel cable with loop + zipper or zipper pro**



max.  
4 kg

**cylinder hook + perlon cord with glider + smartspring**



max.  
15 kg

**cylinder hook + perlon cord with glider + zipper or zipper pro**



max.  
20 kg

**cylinder hook + steel cable with glider + zipper or zipper pro**



max.  
15 kg

**j-rail rod + spring hook**

### Important note regarding warranty and liability

Products of STAS must be installed and used only in strict accordance with the latest version of the STAS picture hanging systems installation guide, available for download at [www.stasgroup.com](http://www.stasgroup.com). It is the responsibility of the installer to select the correct fasteners for the particular installation. Improper installation, misuse, misapplication or otherwise failing to completely follow seller's instructions and warnings may cause product malfunction, property damage or personal injury.

---

### STAS products TÜV certified

STAS strives day after day for products of the highest quality. To guarantee the quality and independence of products, STAS has commissioned TÜV Netherlands for the testing of its products. TÜV Netherlands is an independent and recognized body that assesses the quality of products according to a set standard and has extensive experience in the field of product safety and product inspections. Under the direction of TÜV, a large part of our range of products has been tested for quality and correctness of the specified features. All products where the TÜV logo is shown, have actually been tested by TÜV Netherlands and approved for the capacity that is stated in the features of that product.



### STAS picture hanging systems

Esp 245 | 5633 AD Eindhoven | PO box 1049 | 5602 BA Eindhoven | The Netherlands  
T +31 (0)40 292 48 48 | [info@stasgroup.com](mailto:info@stasgroup.com) | [www.stasgroup.com](http://www.stasgroup.com)